

## Intended use

CROP 1K Spot Blender is a special mixture of solvents (fade-out thinner) dissolve the overspray and to fade out the edges created during spot repair and blendings with 2K-HS-topcoats and clearcoat systems.

## Processing instructions



### Substrates

-

### Pre-treatment / cleansing

-

### Characteristics

Very good dissolving properties  
Ensures smooth transition zones when blending  
Perfectly suitable for spot repairs  
Homogeneous spray result  
Reduces or even avoids polishing work

### Colour / gloss level

Colourless




### Preparation

Before use, shake can vigorously for 1 - 2 minutes!



### Application

Spray to test - spray distance approx. 20 - 30 cm



### Flash-off time

-



### After use

After use, turn can upside down and spray until the valve is clean.

### Processing conditions

From +10 °C and up to 80 % relative humidity. Ensure adequate air ventilation.

### Storage

Can be stored for 2 years in cool and dry places.

## VOC-regulation

EU limit value for the product (cat. B/e): 840 g/l  
This product contains max. 800 g/l of VOC.

## Safety information

See safety data sheet

## Processing instructions

Do not use on thermoplastic substrates.

Immediately after the painting process, spray CROP 1K Spot Blender on to the transition zones (overspray areas).

Apply CROP 1K Spot Blender only in thin, even coats until the rough overspray areas are visibly smoothed out.

Do not apply too thick a coat, as this will result in runners or uneven dissolving.