

Printing date 02.06.2015 *Version number* 99 *Revision:* 02.06.2015

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: MOTIP ZINC SPRAY
- · Article number: 04061
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

Fax: +31 (0)561 694411

e-mail info@nl.motipdupli.com

- · Further information obtainable from: QHSE Department
- 1.4 Emergency telephone number: +31 (0)561-694400 (09:00h 17:00h)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



F+; Extremely flammable

R12: Extremely flammable.



N; Dangerous for the environment

R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R67: Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurised container.

Has a narcotising effect.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)

Trade name: MOTIP ZINC SPRAY

(Contd. of page 1)

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS09

- · Signal word Danger
- · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H410 Very toxic to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether	25-50%
EINECS: 204-003-8 Index number: 603-019-00-8	F+ R12Flam. Gas 1, H220	
Reg.nr.: 01-2119472128-37-xxxx		
CAS: 7440-66-6	zinc powder -zinc dust (stabilized)	25-50%
EINECS: 231-175-3	₩ N R50/53	
Index number: 030-001-01-9	🕸 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
Reg.nr.: 01-2119467174-37-xxxx		
CAS: 67-64-1	acetone	5-10%
EINECS: 200-662-2	★ Xi R36	
Index number: 606-001-00-8	♦ F R11	
Reg.nr.: 01-2119471330-49-xxxx	R6 6-67	
	(b) Flam. Liq. 2, H225 (c) Eye Irrit. 2, H319; STOT SE 3, H336	
		l. on page 3

GB

Printing date 02.06.2015 Version number 99 Revision: 02.06.2015

Trade name: MOTIP ZINC SPRAY

CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	d. of page 5
EC number: 918-668-5	X Xn R65	
Reg.nr.: 01-2119455851-35-xxxx	★ Xi R37	
	N R51/53	
	<u>RI</u> 0-66-67	
	🚸 Flam. Liq. 3, H226	
	♦ Asp. Tox. 1, H304	
	Aquatic Chronic 2, H411	
	♦ STOT SE 3, H335-H336	
CAS: 1330-20-7	xylene	2.5-5%
EINECS: 215-535-7	X Nn R20/21	
Index number: 601-022-00-9	X Xi R38	
Reg.nr.: 01-2119488216-32-xxxx	R10	
	♠ Flam. Liq. 3, H226	
	♠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 1314-13-2	zinc oxide	1-2.5%
EINECS: 215-222-5	₩ N R50/53	
Index number: 030-013-00-7	🕸 Aquatic Acute 1, H400; Aquatic Chronic 1, H410	
Reg.nr.: 01-2119463881-32-xxxx		
CAS: 85711-55-3	Fatty acids, tall-oil, compds. with oleylamine	≤0.1%
EINECS: 288-315-1	★ Xi R43	
Reg.nr.: 01-2119974148-28-xxxx	♦ Skin Sens. 1A, H317	

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Printing date 02.06.2015 Version number 99 Revision: 02.06.2015

Trade name: MOTIP ZINC SPRAY

(Contd. of page 3)

- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingredients w	vith limit values	that require	monitoring a	t the workplace:
11051 000001000 11	TOTAL COLLEGE TOTAL CO		month of the	

115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm Long-term value: 1210 mg/m³, 500 ppm

1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

· Ingredients with biological limit values:

1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

(Contd. on page 5)

Printing date 02.06.2015 Version number 99 Revision: 02.06.2015

Trade name: MOTIP ZINC SPRAY

(Contd. of page 4)

Do not inhale gases / fumes / aerosols.

• Respiratory protection: Not required.

• Protection of hands: Not required.

• Material of gloves Not required.

· Penetration time of glove material Not required.

· Eye protection: Not required.

9.1 Information on basic physical an	d chemical properties
General Information Appearance:	
Form:	Aerosol
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	77 1 , · · 1
Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Not applicable, as aerosol.
Flash point:	< 0 °C (< 32 °F) Not applicable, as aerosol.
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	240 °C (464 °F)
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	3.3 Vol %
Upper:	26.2 Vol %
Vapour pressure at 20 °C (68 °F):	4000 hPa (3000 mm Hg)
Density at 20 °C (68 °F):	$1.095 \ g/cm^3 (9.138 \ lbs/gal)$
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water	
Viscosity:	·
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	59.2 %
EU-VOC:	$648.5 \ g/l$

(Contd. on page 6)

Printing date 02.06.2015 Version number 99 Revision: 02.06.2015

Trade name: MOTIP ZINC SPRAY

(Contd. of page 5)

· 9.2 Other information

No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

I D/I C50	I D/I C50 values relocate for elassification.				
	LD/LC50 values relevant for classification:				
115-10-6 dimethyl ether					
Inhalative	LC50 / 4 h	308 mg/m3 (rat)			
67-64-1 ac	etone				
Oral	LD50	5800 mg/kg (rat)			
Dermal	<i>LD50</i>	20000 mg/kg (rabbit)			
Inhalative	LC50 / 4 h	39 mg/m3 (rat)			
64742-95-	6 Solvent no	uphtha (petroleum), light arom.			
Oral	LD50	3592 mg/kg (rat) (OECD401)			
Dermal	<i>LD50</i>	>3160 mg/kg (rab) (OECD402)			
Inhalative	LC50 / 4 h	>6193 mg/m3 (rat)			
1330-20-7	xylene				
Oral	LD50	3523 mg/kg (rat)			
Dermal	<i>LD50</i>	2000 mg/kg (rabbit)			
Inhalative	LC50 / 4 h	22.1 mg/m3 (rat)			
1314-13-2 zinc oxide					
Oral LD50 7950 mg/kg (mouse)					
Inhalative	LC50	2500 mg/m3 (mouse)			
85711-55-	3 Fatty acid	s, tall-oil, compds. with oleylamine			
Oral	LD50	>2000 mg/kg (rat)			

- · Primary irritant effect:
- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxic	ity:	
115-10-6 dim	ethyl ether	
EC50 / 48 h	>4000 mg/l (daphnia magna)	

(Contd. on page 7)

Printing date 02.06.2015 Version number 99 Revision: 02.06.2015

Trade name: MOTIP ZINC SPRAY

	(Contd. of p
7440-66-6 zinc pow	der -zinc dust (stabilized)
EC50 / 48 h	2.8 mg/l (daphnia magna)
LC50/96 h	0.57 mg/l (daphnia magna)
67-64-1 acetone	
EC50 / 48 h	8800 mg/l (daphnia magna)
LC50/48 h	2262 mg/l (daphnia magna)
LC50/96 h (static)	5540 mg/l (fish)
64742-95-6 Solvent	naphtha (petroleum), light arom.
EC50 / 24 h	150 mg/l (daphnia magna)
EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50/96 h	3.77 mg/l (fish)
1330-20-7 xylene	
EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50/96 h	13.5 mg/l (fish)
1314-13-2 zinc oxid	le
LC50	2.5 mg/l (mouse)
85711-55-3 Fatty ac	cids, tall-oil, compds. with oleylamine
EC50 / 48 h	1.3 mg/l (daphnia magna)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Very toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

		-						<u> </u>
	· European	waste cata	ılogue					
	08 01 11*	waste pai	nt and varni	sh containir	ng org	ganic so	olvents or other dang	gerous substances
I	15 01 04	metallic p	packaging					

- · Uncleaned packaging:
- Recommendation: Non contaminated packagings may be recycled.

a D

Printing date 02.06.2015 Version number 99 Revision: 02.06.2015

Trade name: MOTIP ZINC SPRAY

(Contd. of page 7)

SECTION 14: Transport informate	ton
14.1 UN-Number ADR, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR IMDG	1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS (zinc powder -zinc dust (stabilized), Solvent naphtha (petroleum), light arom.), MARINE POLLUTAN
IATA	AEROSOLS, flammable
14.3 Transport hazard class(es)	
ADR	
Class	2 5F Gases.
Label 	2.1
*	
Class	2.1
Label 	2.1
Class	2.1
Label	2.1
14.4 Packing group ADR, IMDG, IATA	Void
	Product contains environmentally hazardous substances:
14.5 Environmental hazards:	zinc powder -zinc dust (stabilized)
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR):	Symbol (fish and tree)
14.6 Special precautions for user Danger code (Kemler):	Warning: Gases.
EMS Number:	F- D , S - U
14.7 Transport in bulk according to Anne MARPOL73/78 and the IBC Code	ex II of Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E0
Transport category	Not permitted as Excepted Quantity 2

Printing date 02.06.2015 Version number 99 Revision: 02.06.2015

Trade name: MOTIP ZINC SPRAY

(Contd. of page 8)

· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
· UN ''Model Regulation'':	UN1950, AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Relevant phrases
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- R10 Flammable.
- R11 Highly flammable.
- R12 Extremely flammable.
- R20/21 Harmful by inhalation and in contact with skin.
- R36 Irritating to eyes.
- R37 Irritating to respiratory system.
- R38 Irritating to skin.
- R43 May cause sensitisation by skin contact.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- *R67* Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: R&D legislation and regulatory advisor
- · Contact: Mr. K. Smedeman
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

(Contd. on page 10)

Printing date 02.06.2015 Version number 99 Revision: 02.06.2015

Trade name: MOTIP ZINC SPRAY

(Contd. of page 9)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1

Flam. Aerosol 1: Flammable aerosols, Hazard Category 1

Press. Gas C: Gases under pressure: Compressed gas

Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1A: Sensitisation - Skin, Hazard Category 1A

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

* * Data compared to the previous version altered.

CD