

*Tel.*: 0049-(0)6269-95-20 *E-mail*: labor@kwasny.de



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.12.2018 Revision: 04.12.2018

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Aerosol Beispritzverduennung (D)
- · Article number (product ID.): REZ305
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the mixture: painting
- · Uses advised against No further relevant information available.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Peter Kwasny GmbH Heilbronner Str. 96 D-74831 Gundelsheim

· Further information obtainable from: Product safety department

- · 1.4 Emergency telephone number: Tel.:+49 6269 95 20
- · national:

National Poisons Information Service, Birmingham

Tel.: 844 892 0111

· K-Nr. 0001

### SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS05

Printing date 04.12.2018 Revision: 04.12.2018

Trade name: Aerosol Beispritzverduennung (D)

(Contd. of page 1)

### · Signal word Danger

#### · Hazard-determining components of labelling:

cyclohexanone

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.H318 Causes serious eye damage.

#### · Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children. P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.
P302+P352 IF ON SKIN: Wash with plenty of water.
P310 Immediately call a POISON CENTER/doctor.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· Additional information: Without adequate ventilation, explosive atmosphere/gas mix may be created.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

| CAS: 115-10-6   | dimethyl ether  | 50-100% |
|---|---|---------|
| EINECS: 204-065-8<br>Reg.nr.: 01-2119472128-37-xxxx                   | 🏇 Flam. Gas 1, H220; Press. Gas C, H280   |         |
| CAS: 108-94-1<br>EINECS: 203-631-1<br>Reg.nr.: 01-2119453616-35-xxxx  | cyclohexanone<br>♠ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♠ Acute Tox.<br>4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2,<br>H315                  | 5-<10%  |
| CAS: 108-65-6<br>EINECS: 203-603-9<br>Reg.nr.: 01-2119475791-29-xxxx  | 2-methoxy-1-methylethyl acetate  Flam. Liq. 3, H226   | 5-<10%  |
| CAS: 141-78-6<br>EINECS: 205-500-4<br>Reg.nr.: 01-2119475103-46-xxxx  | ethyl acetate<br>Flam. Liq. 2, H225;  Eye Irrit. 2, H319; STOT SE 3,<br>H336  | 5-<10%  |
| CAS: 123-86-4<br>EINECS: 204-658-1<br>Reg.nr.: 01-2119485493-29-xxxx  | n-butyl acetate<br>Flam. Liq. 3, H226; 💠 STOT SE 3, H336  | 5-<10%  |
| CAS: 1330-20-7<br>EINECS: 215-535-7<br>Reg.nr.: 01-2119488216-32-xxxx | xylene, mixture of isomers  Flam. Liq. 3, H226; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 2.5-<5% |

Printing date 04.12.2018 Revision: 04.12.2018

Trade name: Aerosol Beispritzverduennung (D)

|                                | (Cor  | ntd. of page 2) |
|--------------------------------|---|-----------------|
| CAS: 628-63-7                  | pentyl acetate  | 1-<2.5%         |
| EINECS: 211-047-3              | 🚸 Flam. Liq. 3, H226  |                 |
| CAS: 100-41-4                  | ethylbenzene  | 1-<2.5%         |
| EINECS: 202-849-4              | ♠ Flam. Liq. 2, H225; ♦ STOT RE 2, H373; Asp. Tox. 1, H304; ↑ Acute Tox. 4, H332; Aquatic Chronic 3, H412 |                 |
| Reg.nr.: 01-2119489370-35-xxxx | H304; 🕦 Acute Tox. 4, H332; Aquatic Chronic 3, H412   |                 |

<sup>·</sup> Additional information: For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media -
- · Suitable extinguishing agents: Cool container whit water
- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

 $We ar \ protective \ equipment. \ Keep \ unprotected \ persons \ away.$ 

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling Keep away from heat and direct sunlight.
- · Information about fire and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

(Contd. on page 4)

Printing date 04.12.2018 Revision: 04.12.2018

Trade name: Aerosol Beispritzverduennung (D)

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

#### 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm

Long-term value: 766 mg/m³, 400 ppm

#### 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm Sk

#### 141-78-6 ethyl acetate

WEL Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

Zong term value, yer mg/m

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

#### 1330-20-7 xylene, mixture of isomers

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

## 628-63-7 pentyl acetate

WEL Short-term value: 541 mg/m³, 100 ppm Long-term value: 270 mg/m³, 50 ppm

## · Ingredients with biological limit values:

### 1330-20-7 xylene, mixture of isomers

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

(Contd. on page 5)

(Contd. of page 4)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.12.2018 Revision: 04.12.2018

Trade name: Aerosol Beispritzverduennung (D)

· Respiratory protection:



When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Half mask with combination filter, class A1P2 minimum, or breathing mask with outer air supply.

· Protection of hands:

Protective gloves



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Nitrile rubber, NBR
- · Penetration time of glove material

Gloves must be changed after every contamination.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

butyl rubber, 0,7mm

· Eye protection:



Tightly sealed goggles

## SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

**Melting point/freezing point:** Undetermined.

Initial boiling point and boiling range: Not applicable, as aerosol.

· Flash point: <0 °C

Without propellant gas.

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 235 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

(Contd. on page 6)

Printing date 04.12.2018 Revision: 04.12.2018

Trade name: Aerosol Beispritzverduennung (D)

|   | (Contd. of page  |
|---|--|
| · Explosive properties:                   | Product is not explosive. However, formation of explosive air vapour mixtures are possible.  Not determined. |
| · Explosion limits:                       |  |
| Lower:                                    | 3 Vol %  |
| Upper:                                    | 18.6 Vol %   |
| · Vapour pressure at 20 °C:               | 3,400 hPa  |
| · Density:                                | Not determined.  |
| · Relative density                        | Not determined.  |
| · Vapour density                          | Not determined.  |
| · Evaporation rate                        | Not applicable.  |
| · Solubility in / Miscibility with        |  |
| water:                                    | Not miscible or difficult to mix.  |
| · Partition coefficient: n-octanol/water: | Not determined.  |
| · Viscosity:                              |  |
| Dynamic:                                  | Not determined.  |
| Kinematic:                                | Not determined.  |
| · Solvent content:                        |  |
| Organic solvents:                         | 94.0 %   |
| -   | With propellant gas. Content given by weight.  |
| VOC(EU)                                   | 94.04 %  |
| Solids content:                           | 5.0 %  |
| · 9.2 Other information                   | No further relevant information available.   |

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

### ATE (Acute Toxicity Estimates)

| Oral       | LD50     | 17,132 mg/kg (rat)    |
|------------|----------|-----------------------|
| Dermal     |          | 10,580 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 917 mg/l              |

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

(Contd. on page 7)

Printing date 04.12.2018 Revision: 04.12.2018

Trade name: Aerosol Beispritzverduennung (D)

(Contd. of page 6)

- · Serious eye damage/irritation
  - Causes serious eye damage.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Must not reach sewage water or drainage ditch undiluted or unneutralised.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Ikke relevant.
- · 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

15 01 10\* packaging containing residues of or contaminated by hazardous substances

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| SECTION 14: Transport information | m |
|-----------------------------------|---|
|-----------------------------------|---|

| UN1950   |               |
|--|---------------|
| 1950 AEROSOLS<br>AEROSOLS<br>AEROSOLS, flammable |               |
|  | 1950 AEROSOLS |

(Contd. on page 8)

Printing date 04.12.2018 Revision: 04.12.2018

 ${\it Trade name: Aerosol Beispritz verduennung (D)}$ 

|  | (Contd. of pag   |
|--|--|
| 14.3 Transport hazard class(es)            |  |
| ADR  |  |
|  |  |
|  |  |
| 2  |  |
| Class                                      | 2 5F Gases.  |
| Label                                      | 2.1 Gases.   |
| IMDG, IATA                                 |  |
| IMDG, IATA                                 |  |
|  |  |
|  |  |
|  |  |
| Class                                      | 2.1  |
| Label                                      | 2.1  |
| 14.4 Packing group                         |  |
| ADR, IMDG, IATA                            | Void   |
|  | not classified   |
| 14.5 Environmental hazards:                | Not applicable.  |
| 14.6 Special precautions for user          | Warning: Gases.  |
| Danger code (Kemler):                      | -  |
| THE N. I                                   | not classified   |
| EMS Number:                                | F-D,S-U SWI Protected from sources of heat   |
| Stowage Code                               | SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 lit                     |
|  | Category A. For AEROSOLS with a capacity above 1 lit   |
|  | Category B. For WASTE AEROSOLS: Category C, Cle  |
|  | of living quarters.  |
| Segregation Code                           | SG69 For AEROSOLS with a maximum capacity of 1 lit   |
|  | Segregation as for class 9. Stow "separated from" class except for division 1.4. For AEROSOLS with a capac |
|  | above 1 litre: Segregation as for the approprie  |
|  | subdivision of class 2. For WASTE AEROSOL  |
|  | Segregation as for the appropriate subdivision of class 2.   |
| 14.7 Transport in bulk according to Anne   | ex II of   |
| Marpol and the IBC Code                    | Not applicable.  |
| Transport/Additional information:          |  |
| ADR  |  |
| Limited quantities (LQ)                    | IL   |
| Excepted quantities (EQ)                   | Code: E0   |
| Transport estacory                         | Not permitted as Excepted Quantity   |
| Transport category Tunnel restriction code | 2<br>D   |
|  |  |
| IMDG Limited quantities (LQ)               | IL   |
| Excepted quantities (EQ)                   | Code: E0   |
|  | Not permitted as Excepted Quantity   |
|  | (Contd. on page  |

Printing date 04.12.2018 Revision: 04.12.2018

Trade name: Aerosol Beispritzverduennung (D)

(Contd. of page 8)

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Technical instructions (air):

| Class | Share in % |
|-------|------------|
| NK    | 50-100     |

- · Waterhazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)

(Contd. of page 9)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 04.12.2018 Revision: 04.12.2018

### Trade name: Aerosol Beispritzverduennung (D)

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3